WORLD BEATING PRODUCT LINE WORLD





BUILT TO LAST!

QUALITY, RELIABILITY, LONG LIFE - THESE WERE THE OBJECTIVES OF ART BARTELL WHEN HE DESIGNED AND ENGINEERED HIS POWER TROWEL SOME 50 YEARS AGO. OUR MACHINES ARE BUILT FROM THE BOTTOM UP TO THE SAME TRIED AND TESTED DESIGN AND QUALITY PARAMETERS. THE RESULT IS A WELL BALANCED, RELIABLE, HEAVY DUTY WORKHORSE THAT WILL GIVE YOU YEARS OF SERVICE AND A GREAT RETURN ON YOUR CAPITAL INVESTMENT.





- CONTOURED HANDLE FOR MAXIMUM CONTROL AND COMFORT
- HANDLE IS LATERALLY WELDED TRI TUBE FOR MAX STRENGTH
- CONTROL CABLES AND WIRES RUN INSIDE THE HANDLE FOR MAXIMUM PROTECTION
- DUAL SAFETY STOP SYSTEMS
- LIFTING HOOK
- CHROMED GUARD RING AND HANDLE FOR EASY CLEANING
- LIFTING HOOK AS STANDARD
- PRECISION MACHINED BRONZE GEAR TAILORED TO A HARDENED GROUND WORM GEAR
- IMPACT RESISTANT ALUMINIUM GEARBOX
- TAPERED MAINSHAFT FOR PERFECT LOCKING FIT TO SPIDER PLATE
- PRECISON MACHINED SPIDER PLATE AND MATCHED TROWEL ARMS TO VERY FINE TOLERANCES ENSURE MINIMUM WEAR AND A LONG SERVICE LIFE
- TROWEL ARMS GREASE GROOVED ENSURING GREASE MOVES ALONG THE ENTIRE CONTACT SURFACE **ENSURING CONTINUAL FREE MOVEMENT AND** MINIMAL WEAR. ▶▶▶







FINISHING **CLOSE TO** THE EDGE

WITH A BT EDGER MACHINE

- BT EDGER MACHINES TAKE THE HARD WORK AWAY FROM FINISHING CLOSE UP TO WALLS AND COLUMNS
- ROTATING RING WITH RUBBER PROTECTED EDGE ALLOWS THE MACHINE TO RUN ALONG THE WALL
- THE BLADES SIT DIRECTLY TO THE EDGE OF THE GUARD RING SO THAT THEY FINISH TIGHT TO THE WALL
- A GOOD MACHINE FOR SMALL TIGHT AREAS OF FINISHING



60 CM DIA EDGER MACHINE ELECTRIC MOTOR







BT900-2PFH24 2 x 90 cm LOW RIDE ON FLOAT PAN MACHINE ALSO AVAILABLE AS AN OVERLAPPER




THE POWER TO FINISH FLOORS FAST

- HEAVY DUTY GEARBOXES 12 MONTH GUARANTEE
- PRECISION MACHINED SPIDER ASSEMBLIES TO EXACT TOLERANCES -GIVING MINIMAL WEAR
- SIMPLE YET STRONG DRIVE TRAIN WITH TRIED AND TESTED BLM TYPE CLUTCH
- EASY POSITIVE STEERING
- SPRAY SYSTEM, ADJUSTABLE SEAT,4 X RUNNING LIGHTS, ENGINE HOUR METER ALL
- OPTIONAL TRANSPORT DOLLEY FOR SITE USE
- 4 POINT CRANE SLINGING LIFT POINTS
- DIESEL RIDER WITH INBUILT SEAT SUSPENSION AND IPHONE USB CHARGER
- DRINK HOLDER FITTED AS STANDARD



BETON TROWEL CONSUMABLES

BETON TROWEL QUALITY TROWEL BLADES AND FLOAT PANS TO FIT MOST MAKE OF MACHINE ON THE MARKET. MANUFACTURED TO THE HIGHEST STANDARDS FROM THE BEST MATERIALS.





Wide Finish Shoes



Combination Blades



Edger Blades



Float Shoes



Special Blades



Float Pans



Plastic Blades



Grinding Block Holder





ASK ABOUT OUR RANGE OF CONCRETE HAND TOOLS



WWW.BETONTROWEL.COM

CONCRETE CUTTING AND SEALING

BETON CONCRETE SAW CS500

THE **CS500** FLOOR SAW IS A ROBUSTLY CONSTRUCTED, POWERFUL MACHINE THAT IS DESIGNED FOR ALL TYPES OF CONCRETE AND ASPHALT REPAIR WORK, AND FEATURES A GENEROUSLY SIZED BUILT IN INTEGRAL WATER TANK THAT PERMITS WET CUTTING TO TAKE PLACE ALMOST ANYWHERE.

- CUTTING ON RIGHT HAND SIDE ONLY.
- HEAVY DUTY JIG WELDED STEEL CONSTRUCTION.


ENGINE H	HONDA PETROL
POWER 1	13 HP
MAXIMUM BLADE CAPACITY 1	18" / 500 MM
MAXIMUM CUTTING DEPTH 1	165 MM
WEIGHT 1	140 KG



SEALING JOINT

THE PERFECT PRODUCT FOR JOINT SEALING.
THE PLASTIC SEALER OFFERS GOOD ELASTICITY IN THE JOINT AS WELL AS PROVIDING A PLEASING FINISH TO THE FLOOR.





STANDARD GREY COLORUPON REQUEST ANY OTHER COLOR AVAILABLE.

MINUMUM QUANTITY ORDER 50 ROLLS.

STANDARD SIZES

DISC TYPE	DISCTHICKNESS	JOINT WIDTH	ROLL LENGTH
DIAMOND CUT	2,4 MM	3,0 MM	400 M
		3,5 MM	400 M
		3,8 MM	400 M
DIAMOND CUT	2,8 MM	4,0 MM	300 M
		4,2 MM	300 M
DIAMOND CUT	3,2 MM	4,6 MM	300 M
ABRASIVE	4,0 MM	5,2 MM	200 M
		5,4 MM	200 M
		5,6 MM	200 M

JOINT LAYING TROLLEY

THE TROLLEY ALLOWS EASY AND RAPID APPLICATION OF THE PLASTIC SEALANT.
JOINTS CAN BE SEALED IN THE TIME IT TAKES TO WALK THE LENGTH OF THE JOINT.

DIMENSIONS (CM) 60 X 35 X 93



CONCRETE TOPPING MATERIAL SPREADER



BT2WMS

- HANDLE FOLDS DOWN FOR EASE OF TRANSPORTATION
- FOLD DOWN STAND FOR EASE OF MATERIAL LOADING
- LOW DOWN MATERIAL DISCHARGE AVOIDS HAZARDOUS AIRBORNE DUST
- EXACT MATERIAL MEASUREMENT PER SQUARE METER SAVES MATERIAL COST AND MEETS EXACT JOB SPECIFICATION
- HOPPER TAKES 100 KG OF MATERIAL
- DISCHARGE RANGE 1 TO 6 KG
- WHEEL AXLES DRIVE HOPPER BLADES
- EACH WHEEL AXLE IS INDEPENDENT FOR EASY TURNING IN TIGHT SPACES

BTSP8H - BTSP8E

- 200 MM CUTTING WIDTH
- FINGER TIP CUTTER HEIGHT CONTROL
- VACUUM OUTLET FITTED AT BUSINESS END
- ENGINE DECK ANTI-VIBRATION ISOLATED FOR LONGER ENGINE LIFE
- 60 KG WEIGHT FOR EFFECTIVE SCARRIFYING
- TUNGSTEN CARBIDE CUTTERS FITTED AS STANDARD
- HEAVY DUTY CUTTER CAGE WITH STRONG CENTRE SUPPORT
- FAST, EASY, EFFICIENT CUTTER CHANGES
- HONDA GX160 5.5HP ENGINE OR 2.2 KW, 230V ELECTRIC, 50HZ



DEALER

BETON TROWEL n.v.

tel. +32 (0)52 315 350 tel. +32 (0)52 315 351 fax +32 (0)52 303 739 info@betontrowel.com www.betontrowel.com Niiverheidsstraat 11

B-1840 Londerzeel - Belgium

