

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY



BETON TROWEL n.v.

tel. +32 (0)52 315 350
tel. +32 (0)52 315 351
fax +32 (0)52 303 739
info@betontrowel.com
www.betontrowel.com

Nijverheidsstraat 10
BE-1840 Londerzeel - Belgium



**BTHFC
+
BTFC**

BT HIGH FREQUENCY VIBRATOR CONVERTORS

BT FREQUENCY CONVERTORS ARE THE SAFE WAY TO USE HIGH FREQUENCY VIBRATORS AND THEY REDUCE INCOMING 3 PHASE OR SINGLE PHASE POWER AT THE VIBRATOR HEAD TO 42V/200HZ

- CONVERTOR UNITS MOUNTED IN PROTECTICE STEEL FRAME
- SINGLE AND THREE PHASE POWER UNITS
- UNITS DRIVING 1, 2 AND 4 VIBRATORS

SPECIFICATIONS

MODEL	DIA	FREQUENCY	AMPLITUDE	HOSE	CABLE	POWER	AMPS	KN
BTHFC35/5	35mm	12000	1,8	5m	10m	42V/3-200hZ	8	1
BTHFC35/12	35mm	12000	1,8	12m	10m	42V/3-200hZ	8	1
BTHFC45/5	45mm	12000	2	5m	10m	42V/3-200hZ	11	2,6
BTHFC45/12	45mm	12000	2	12m	10m	42V/3-200hZ	11	2,6
BTHFC60/5	60mm	12000	2,2	5m	10m	42V/3-200hZ	16	2,2
BTHFC60/12	60mm	12000	2,2	12m	10m	42V/3-200hZ	16	2,2

SPECIFICATIONS

MODEL	CAPACITY	INPUT PH/HZ/V/A	OUTPUT	WEIGHT	QTY VIBS PER UNIT
BTFC200/18/2	1.8 KVA	3/50/380/2.8	3/200/48/22	37 Kg	2
BTFC200/45/4	4.5 KVA	3/50/380/8.3	3/200/48/54	78 Kg	4
BTFC200/11/1-D	1.1 KVA	1/50/220/2.8	3/200/48/11	27 Kg	1
BTFC200/25/2-D	2.5 KVA	1/50/220/2.8	3/200/48/25	37 Kg	2

