

BETON TROWEL

CONCRETE FINISHING
& COMPACTION



SOLAR LIGHT TOWER 4VS200



- IP65 LED lights
- Galvanized mast, 359° rotating manually
- Durable & efficient solar module
- Deep cycle and maintenance-free lead-acid batteries
- Retractable & adjustable supporting wheel tow bar
- Four 5000lb individual stabilizing legs
- 13" rim with regular tires

BETON TROWEL

CONCRETE FINISHING & COMPACTION



| Model | 4VS200 |
|---|---|
| Light style & IP grade | LED & IP65 |
| Lights number & power | 4*50W |
| LED luminous efficiency LM/W) | 110 (total 22000) |
| LED life-span (Hrs) | > 50000 |
| Batteries style | Maintenance-free lead-acid batteries |
| Batteries number & capacity (Ah) | 4x 225 |
| Battery & lights rated voltage (V, DC) | 24 |
| Battery charger (V, DC) | 24 |
| Solar module number & most power (W) | 2 x 245 |
| Solar module tilt adjusting | 0° ~ 25° |
| Solar module tilt adjusting method | Manually |
| Length x Width x Height (mm) | 3200 x 1300 x 1950 |
| Weight without any options (kg) | Approx: 600KG |
| Height (Mast extended fully, m) | 5,5 |
| Mast extention | Manually |
| Light tilt | Manually |
| Mast rotate | 359° manual rotation with self locking |
| Mast sections number | 5 |
| Trailer suspension system & wheel rim | single axle without brake |
| Stabilizing legs & number | 4 pcs extendable bar with manually retractable jacks |
| Tow adapter | 2" or 50 mm ball adapter |
| Tail lights | Tail reflector |
| Controller | Smargen controller (auto on/off from sunrise to sunset) |
| Max. load quantity in a 40 feet container | 7 |