BETON TROVEL CONCRETE FINISHING & COMPACTION

BTPT75H PORTATROWEL

- Blade pitch function of up to 25 degrees
- Allows for the PortaTrowel to be used for initial floating of the wet concrete right trough to final finishing Control from up to 6m away
- Variable length pole/stick for optimised control when finishing concrete (Clip together handles sold separately)
- Easy Control directional steering function
- Allows for precise movement of the PortaTrowel by twisting the handle from side to side
- Lightweight design
- Improved operator comfort and safety
- Honda GX35 engine
- Hassle free operation
- Low engine emissions

SPECIFICATIONS:

• Trowel diameter: 750mm – 30"

ROWEL.COM

- Operating weight: 20 kg
- Number of blades: 4
- Speed range: 40-70 RPM
- Blade pitch max: 25 deg
- Engine make: Honda
- Engine model: GX35
- Max rated power: 1.5 Hp
- Fuel type: petrol
- Shipping dimensions: 775x775x480 mm

CE

• Shipping weight: 25 kg

BETON TROWEL BV - Nijverheidsstraat 10 - B-1840 Londerzeel - Belgium Tel. +32 (0)52 315 350 - Fax +32 (0)52 315 359 - info@betontrowel.com - www.betontrowel.com