

BETON TROWEL

CONCRETE FINISHING
& COMPACTION



BT SPRAYERS

BTSPRAY06L & BTSPRAY10L: these professional compression sprayers, 6 & 10 l, are particularly suitable for professional users. The tanks are made of polyester-coated steel and can be carried on the side or back with padded carrying strap. The 50 cm long brass spray wand with flat jet nozzle 80-01 is 360° rotatable and the 2.5 m long spiral hose with safety interlock ensures optimal reach for working. With safety valve and replaceable pressure gauge with indicator.

Other features such as pump, spray wand and extension wand holders and a stocked spare parts compartment on the device offer a comprehensive set of equipment for the device. FPM seals provide excellent resistance to many construction chemicals such as release agents and forming oil.

- **Ideal for:** Construction industry, Structural and civil engineering, Highway construction
- **Applications:** Concrete curing, concrete spraying, Concrete formworking, Priming, Impregnating, Preserving, Lubricating, Pre-wetting
- **Scope of delivery general:** tank, Hose, shut-off valve, Spray wand, Nozzle(s), Carrying strap, Instructions for use, Pump.

SPECIFICATIONS:

- Fill Capacity: 6 & 10 l
- Total contents: 9 & 13 l
- Weight: 4,8 & 5,5 Kg
- Max. operating pressure: 6 bar/ 88 psi / 0.6 MPa
- Hose length: 250 cm
- Hose diameter: D6
- Nozzle type: Spray nozzle, Flat jet rectangular distribution, Filter
- Nozzle material: Plastic
- Shut-off valve connection: for spiral hose D6
- Shut-off valve characteristics with filter, with safety interlock
- Compressed air filler valve: can be retrofitted

