



www.betontrowel.com
 Nijverheidsstraat 10
 BE-1840 Londerzeel - Belgium

Tel. +32 (0)52 315 350
 Tel. +32 (0)52 315 351
 Fax +32 (0)52 315 359
 info@betontrowel.com

Specification

Photo		Data	Name	LED flood light
			Model No.	BTPAL0310L
			Power	LED 300W
			Installation mode	U bracket
			Work temperature	-40°C~50°C
			Work voltage	AC100-277V 50/60Hz
			Power Factor	>0.95
			Rated life	50000 hrs
		Standards	IP	IP67
		Main parts	Housing	Aluminum extrusion profiles
Radiating module	Aluminum radiator			
Optical part	Optical lens			
Color	Silver			
Photometrics		Optical Parameter	Beam angle	60°
		Luminous flux	43500Lm@5700K	
		Color temperature	5700±300K	
		CRI	RA≥70@5700K	
		Light Source	LED Chip	Lumileds 5050
			Module Specification	28PCS×4
Accessories		Driver	Brand	Inventronics
		Installation mode	External	
		Specification	Constant Current	
	Packing information	Carton size	390*390*235MM	
		Net Weight(Kg)	8. 2KG	
		Accessories	Installation instruction, Certificate of Approval	
		Packing	Carton	
Dimension				